

INDION® 180

Description

INDION 180 resin is a macroporous strongly acidic cation exchanger developed for heterogeneous acid catalytic application.

INDION 180 is supplied in dry form as opaque, grey coloured spherical beads. A proper mix of high cross linking and porosity gives this product outstanding physical stability with high concentration of acid groups.

The unique structure of INDION 180 provides genuine porosity and a strong matrix together, with small volume change in different solutions and solvents. The large surface area leads to high catalytic activity. The functional groups throughout the entire structure are readily accessible to liquid or gaseous reactants thus ensuring efficient performance. The main applications are alkylation, esterification, etherification, condensation, hydrolysis and also for specialised applications such as MTBE.

Characteristics

Appearance : Opaque grey to dark grey beads

Matrix : Styrene divinylbenzene copolymer

Functional Group : Sulphonic acid

Ionic form as supplied : Hydrogen

Concentration of acid sites : 5.0 meq/dry g, minimum

Moisture content : 1.0 %, maximum

Particle size range : 0.42 to 1.2 mm

> 1.2 mm : 5.0%, maximum

< 0.42 mm : 5.0%, maximum

Maximum operating temperature : 130 °C

Operating pH range : 0 to 7

Reuse of INDION 180

On completion of the catalytic reaction, the resin should be filtered off the products. The solvent as well as unreacted reactants associated with the resin should be washed off by rinsing with either solvent or one of the reactants. These washings can then be reused in subsequent batch processes. If water formation exists in the reaction after filtration, dry the resin. This can be carried out in an oven at about 90°C to 100°C for 6 to 10 hours to reduce moisture content to less than 5%.

Packing

HDPE carbouys with inner double plastic liner bags

 $25/50 \, \text{kgs}$

Storage

Ion exchange resin catalysts are hygroscopic in nature. Therefore it is essential to store the dry INDION 180 in tightly packed containers, to prevent absorption of atmospheric moisture. In case moisture has been absorbed, it can be dried at 90°C - 100°C as mentioned above.

Safety

Acid and alkali solutions used for regeneration are corrosive and should be handled in a manner that will prevent eye and skin contact. If any oxidising agents are used, necessary safety precautions should be observed to avoid accidents and damage to the resin.

INDION range of ion exchange resins are produced in state-of-the-art ISO 9001 and ISO 14001 certified manufacturing facility at Ankleshwar, Gujarat.

To the best of our knowledge the information contained in this publication is accurate. Ion Exchange (India) Ltd. maintains a policy of continuous development and reserves the right to amend the information given herein without notice.

INDION is the registered trademark of Ion Exchange (India) Ltd.

ION EXCHANGE (INDIA) LTD.

Corporate Office

Ion House, Dr. E. Moses Road, Mahalaxmi, Mumbai 400 011

Tel: +91 22 3989 0909 | Fax: +91 22 2493 8737

E-mail: ieil@ionexchange.co.in

International Division

R -14, T.T.C MIDC, Thane - Belapur Road, Rabale, Navi Mumbai 400 701

Tel: +91 22 3989 0909 / 3913 2400 | Fax: +91 22 2769 7918

E-mail: export.sales@ionexchange.co.in

OFFICES

| Regional | Telephone | Fax | E-mail |
|---------------|------------------------------|------------------|-------------------------------|
| Chennai | +91 44 3989 0909 / 3910 2900 | +91 44 2815 3361 | checro@ionexchange.co.in |
| Delhi | +91 11 3989 0909 / 3054 3200 | +91 11 2577 4837 | delcro@ionexchange.co.in |
| Kolkata | +91 33 3989 0909 / 3043 3400 | +91 33 2400 4345 | calcro@ionexchange.co.in |
| Vashi | +91 22 3989 0909 / 3913 2300 | +91 22 2788 9839 | mumcro@ionexchange.co.in |
| Branch | | | |
| Bengaluru | +91 80 2204 2888 | +91 80 2853 2002 | bngcro@ionexchange.co.in |
| Bhubaneswar | +91 674 326 9525 / 257 1491 | | bbsr@ionexchange.co.in |
| Chandigarh | +91 172 274 5011 | +91 172 274 4594 | delcro@ionexchange.co.in |
| Hyderabad | +91 40 3066 3101 / 02 / 03 | +91 40 3066 3104 | hydcro@ionexchange.co.in |
| Lucknow | +91 522 319 9911 | +91 11 2577 4837 | lko.general@ionexchange.co.in |
| Vadodara | +91 265 302 7489 / 90 | +91 265 2352 932 | brdcro@ionexchange.co.in |
| Visakhapatnam | +91 891 324 6253 | | sales.vizag@ionexchange.co.in |

Factories: Ankleshwar | Hosur | Patancheru | Rabale | Verna

All India Service and Dealer Network